

### MODEL 508 - BALL CHECK

- Cast iron body with epoxy coating
- Corrosion resistant phenolic "sinking" ball
- Threaded female x female connection
- 2 bolt access cover

SIZE	PART NO.	WGT lbs	LIST PRICE-A
1"	173232	3.0	323.31
1-1/4"	173233	4.2	335.36
1-1/2"	173234	5.4	347.77
2"	173235	8.0	378.33
2-1/2"	173236	13.8	904.62
3"	172044	30.0	953.56
4**	172045	45.0	1425.51

\*CONNECTION IS FLANGED ANSI 125

NOTE: 3" and 4" has no access cover



Temp. Max 180°F (80°C)  
Pressure Max 150 PSI

### MODELS 208T/208S - PVC BALL CHECK

- Corrosion resistant PVC body
- Threaded female x female connection
- NITRILE (Buna-N) self-cleaning ball
- E-Z access port with nitrile (Buna-N) seal

SIZE	PART NO.	WGT lbs	LIST PRICE-A
1"	172131T	1.0	81.87
1-1/4"	172132T	1.0	82.62
1-1/2"	172133T	2.0	129.42
2"	172134T	2.0	129.42

Also available with socket weld (slip) (Model 208S)

Contact your Sales Rep for information



Temp Max 150°F (51°C)  
Pressure Max 100 PSI

### MODEL 208 - BALL CHECK

- Cast iron body with epoxy coating and clean-out port
- Threaded female x female connection
- Features NITRILE (Buna-N) "Sinking" ball

SIZE	PART NO.	WGT lbs	LIST PRICE-A
1-1/4"	172141	4.5	206.38
2"	172142	9.0	238.80



Temp Max 150°F (51°C)  
Pressure Max 150 PSI