

## #304 STAINLESS STEEL RELIEF VALVES (NON-ADJUSTABLE)

Pressure relief valves are recommended for all cold water system installations - to protect against damage to piping and pressure tanks. Set at 75 PSI, (+) 15% setting accuracy, field adjustments are not recommended.

PART NO.	SIZE		PRESSURE RANGE	QUANTITY		LIST PRICE-A
	IN	OUT		CTN	CASE	
SSRVN05-075	1/2" MPT	1/2" FPT	Set at 75 PSI	10	100	14.85
SSRVN07-075	3/4" MPT	1/2" FPT	Set at 75 PSI	10	100	15.85
SSRVN05-100	1/2" MPT	1/2" FPT	Set at 100 PSI	10	100	14.85
SSRVN07-100	3/4" MPT	1/2" FPT	Set at 100 PSI	10	100	15.85



## PVC RELIEF VALVES

Pressure relief valves are recommended for all cold water system installations - to protect against damage to piping and pressure tanks. Set at 75 PSI, (+) 15% setting accuracy, field adjustments are not recommended.

- PVC material
- Designed for low maintenance
- Factory Preset to 75 PSI (Adjustable to 150 PSI)
- High quality Stainless Steel spring

PART NO.	SIZE	PRESSURE RANGE	QUANTITY		LIST PRICE-A
			CTN	CASE	
PVCRVN05-75150	1/2"	Set at 75 PSI	_0	_40	4.77



## RELIEF VALVE INFORMATION

Valves will be sold at factory pre-set PSI only. While field adjustments are not recommended we have included the approximate range information shown above which has been provided by the manufacturer(s). However, any changes made to the pre-set pressure is entirely at the risk of the person(s) / company who makes the adjustment. Any changes made should be thoroughly tested for accuracy at time of installation. Neither the manufacturer or Boshart Industries Inc. will assume any liability or responsibility caused as a result of adjusting the relief valve setting.

If the pressure setting is adjusted, it will void any warranty or return of the product.

Relief valves must be installed so that they drain to a floor drain, sump or other safe location with an air break. If an outlet pipe is used then it must be at least the same diameter as the relief valve outlet.

Cold water use only.

## SNIFTER (AIR / TANK) VALVES

PART NO.	DESCRIPTION	WORKING PRESSURE	WORKING TEMP. (°F)	OPENING QUANTITY		LIST PRICE-A
				PRESSURE	BAG CASE	
SV-0	1/8" MPT Snifter Valve SV-0 manufactured with light spring required for shallow well pump and bleeder systems	15-150 PSI	-10° To +165°	3 PSI	10 100	1.29
SV-1	1/4" MPT Tank Valve General Purpose	0-100 PSI Peak of 300	-40° To +5°	60 PSI	10 100	1.83
SV-CAP	Black Flexible Plastic Cap - has no sealing unit Bags of 10/100				1 1000	
SV-CAP-M	Chrome plated steel cap c/w valve core driver feature Bags of 10/100				1 1000	



Valves must be ordered in multiples of 10

## BLEEDER ORIFICES

- BOB3** - 3/4" Brass
- Will** not corrode or stick
- Rapid** opening and closing valve for submersible pumps
- Complete** closure prevents loss of pumping volume

- BOR4** - 1" rubber
- Non-corrosive** bleeder
- Fast** bleed through its large opening

PART NO.	LIST PRICE-A
BOB3	19.53



PART NO.	LIST PRICE-A
BOR4	2.20

