

ADJUSTABLE cABLE wEIGHt

This 1.34 lbs (610 grams) cable weight allows for easy adjustment of the tether length on sensor/non-internally weighted float switches, manufactured from zinc plated cast iron for superior corrosion resistance, with two internal grip rings to prevent slippage on the cord. Constructed in two halves which are held together with stainless steel bolts which thread directly into the castings, the bolt heads are countersunk to ensure that no debris catches on the bolt.

PART NO.	DEScRIPTION	LIST PRICe-A
890-AW-CI	Adjustable Cable Weight	15.46



AccESSORIES

PART NO.	DEScRIPTION	BAG qTy	LIST PRICe-A	
890-CC516BK	5/16" Black Nylon Cable Clip	100	0.90 each	Must be ordered in bag quantities
It is highly recommended that this cable clip be installed to secure the power cord of a float switch, pump or liquid level alarm to either the wall or electrical outlet using the outlet faceplate screw. To prevent plug from being accidentally disconnected from the electrical outlet.				

890-CRT14BK	14" 50# Button Release UV Black	100	0.51 each	Must be ordered in bag quantities
Releasable cable ties are ideal for fastening the the float switch cord at the tether point. It's release feature allows the tie to be re-opened for easy adjustment of the tether length to change the pumping range for either more or less distance between the turn-on and turn-off levels.				



The cable clamp and cable tie are now included with the 860 and 870 series float switches and 850L and 850H level alarms. Bosharts has added the two items to meet or exceed industry standards in the Float and Alarm business.

TAPPED PITLESS ADAPTERS - FOR UNDERgROUND TANKS / DIRTY wATER

PART NO.	SIZE	TAPPING	qUANTITY		LIST PRICe-A
			cTN	cASE	
•1-1/4" and 2" Tapped Pitless are for dirty water applications. The 1/4" FPT tapping provides a means to connect a 1/4" pipe to the pitless to allow easy removal of the pitless unit and pump. The pipe is guided by a rail/guide system that aligns the pitless elbow with the pitless slide when reinstalling (railing or guide system not included).					
1-1/4" units are used with grinder pumps					
PA-125-T	1-1/4" Bronze	1/4"	1	10	115.59
P-125-SS-T	1-1/4" Stainless Steel	1/4"	1	10	177.16
2" units are used with all other sewage pumps					
PA-200-T	2" Bronze	1/4"	1	4	257.90
P-200-SS-T	2" Stainless Steel	1/4"	1	4	464.47



Also Available. Please see Section 11 for pricing.

•1" Tapped Pitless are for underground water well tank installations. The 1/4" FPT tapping provides a means to connect poly tubing to the pressure switch which is located near the buried tank.

PA-800-T	1" Bronze	1/4"	1	16
P-100-SS-T	1" Stainless Steel	1/4"	1	16