

SUBMERSIBLE TORQUE ARRESTORS

- Precision moulded to exacting specifications
- Protects submersible pumps from starting torque damage
- Deluxe model is field-adjustable to hold pump centred in well
- Snug fit in all well casings from 4" to 8" I.D.
- Two piece design installs quickly
- Eliminates flashing problems
- Securely fasten to 1" or 1-1/4" drop pipe with the stainless steel clamps provided

SPECIAL FEATURE: Infinite adjustment feature enables installer to obtain proper fit, eliminating damage to pumps due to high starting torque.

PART NO.	COLOUR	CASING SIZE	DROP PIPE SIZE	UNIT WGT	QUANTITY CASE	LIST PRICE-A
STANDARD						
TA-48-BLK	Black	4" to 8"	1" to 1-1/4"	1.0 lb	10	13.21
TA-48-GREEN	Green	4" to 8"	1" to 1-1/4"	1.0 lb	10	13.21
DELUXE						
TA-48D-BLK	Black	4" to 8"	1" to 1-1/4"	1.4 lb	10	14.30
TA-48D-GREEN	Green	4" to 8"	1" to 1-1/4"	1.4 lb	10	14.30
THREE PIECE DESIGN						
TA20-68D-BLK	Black	6" to 8"	2"		5	32.95



TORQUE ARRESTOR "SPIDER"

Sizes 1" - 2" - BII

- Sizes 1" - 2" have unique wire guard feature
- Easily secured to drop pipes with stainless steel clamp (not included)
- Casing size clearly marked on torques for ease of cutting to size
- Molded from strong Styrene Butadiene Rubber (SBR)



Sizes 2-1/2" - 3"

- Moulded of thermoplastic rubber
- Easily secured to drop pipe with stainless steel clamp (Not Included)
- Handy number marking for ease of cutting to casing size

1" to 2"
Design



2-1/2" to 3"
Design



PART NO.	FITS DROP PIPE IPS	FITS CASING ID	QUANTITY CASE	SUGGESTED CLAMP SIZE	LIST PRICE-A
TAS46-10	1"	4" to 6"	25	SSC8740	3.95
TAS46-12	1-1/4"	4" to 6"	25	SSC8740	3.95
TAS46-15	1-1/2"	4" to 6"	25	SSC8740	3.69
TAS46-20	2"	4" to 6"	25	SSC8740	3.92
TAS46-25	2-1/2"	4" to 6"	25	SSC8740	8.91
TAS46-30	3"	4" to 6"	25	SSC8772	14.60

CABLE TIES

- Natural Nylon 6/6 is not UV resistant and used mainly indoors
- Black Nylon 6/6 is UV resistant for both indoors and outdoors applications
- Carbon has been added to Nylon 6/6 to make it UV resistant



NATURAL PART NO.	LIST PRICE-A	BLACK PART NO.	LIST PRICE-A	LENGTH	TENSILE STRENGTH	MAX. DIA.	APPROX. WIDTH	PCS/BAG
CT018-04	0.02	CTW018-04	0.02	4.0"	18 lbs	5/8"	.10"	100
CT030-05.6	0.04	CTW030-05.6	0.04	5.6"	40 lbs	1 1/4"	.13"	100
CT040-08.5	0.05	CTW040-08.5	0.05	8.5"	40 lbs	2"	.13"	100
CT040-11.5	0.08	CTW040-11.5	0.09	11.5"	40 lbs	3"	.146"	100
CT040-14.5	0.11	CTW040-14.5	0.12	14.5"	50 lbs	4"	.146"	100

HEAVY DUTY LASHING CABLE TIES (ULTRA VIOLET LIGHT RESISTANT)

CTW120-14.2	0.23	14.2"	120 lbs	4"	.30"	100
CTW120-24.2	0.45	24.2"	175 lbs	7"	.30"	50
CTW175-36	0.56	36.0"	175 lbs	10 3/4"	.345"	50
CTW175-41	1.16	41.0"	175 lbs	12"	.345"	50