

## WCC SERIES BII CONDUIT WELL CAPS

### ALUMINUM CONDUIT CAPS

- Heavy duty design for added durability
- Designed to provide extra clearance for pump cable
- Three stainless steel set screws for secure fit to well casing
- One stainless steel set screw to secure conduit pipe
- A well log is provided inside each cap to record installation data/specifications



WCC-A06-BLUE  
(powder coat paint)

PART NO.	CASING SIZE (IN.)		CONDUIT PIPE SIZE	UNIT wgT (lbs)	QTY CASE	LIST PRICE-A
	I.D.	O.D.				
WCC-A04	4"	4-1/2"	1"	1.25	36	14.31
WCC-A045	4-1/2"	5"	1"	1.20	30	16.81
WCC-A05	5"	5-9/16"	1"	1.40	30	17.39
WCC-A056	5-5/8"	6"	1"	1.50	30	18.22
WCC-A06	6"	6-5/8"	1"	1.75	20	18.20
WCC-A06-BLUE	6"	6-5/8"	1"	1.75	20	22.74
WCC-A066	6-5/8"	7"	1"	1.80	20	20.48
WCC-A08	8"	8-5/8"	1"	2.50	16	34.42
WCC-A10	10"	10-3/4"	1"	3.00	10	71.96

## WCCL SERIES BII ALUMINUM LOCKING CONDUIT CAPS

- Stainless steel set screws
- Locking feature provides a secure/tamper-proof installation



Note: Locks not included.  
For illustration purposes only.

PART NO.	CASING SIZE (IN)		CONDUIT PIPE SIZE	UNIT wgT-lbs	CASE QTY	LIST PRICE-A
	I.D.	O.D.				
WCCL-A06	6"	6-5/8"	1"	2.0	20	18.87

## CC SERIES CAST IRON CONDUIT CAPS

- Heavy cast iron construction
- Quick installation
- Blue painted finish
- packaged individually



PART NO.	CASING SIZE (IN)		CONDUIT PIPE SIZE	QUANTITY		CTN/CASE SHIPPING wgT-lbs	LIST PRICE-A
	I.D.	O.D.		CTN	CASE		
CC-6-CI	6, 6-1/4"	6-5/8"	1"	1	8	5/35	19.36

## WCP SERIES BII PLAIN WELL CAPS

### ALUMINUM PLAIN CAPS

- Heavy duty design for added durability
- Uses three stainless steel set screws for secure fit to well casing
- A well log is provided inside each cap to record installation data/specifications



WCp Series

PART NO.	CASING SIZE (IN.)		UNIT wgT (lbs)	QTY CASE	LIST PRICE-A
	I.D.	O.D.			
pC-4	4"	4-1/2"	0.87	36	21.61
WCp-A05	5"	5-9/16"	1.20	30	12.68
pC-566 (2-STEP)	5-5/8"	UppER 6"	1.87	21	43.24
	6"	LOWER 6-5/8"			
WCp-A06	6"	6-5/8"	1.50	24	16.30
pC-66	6-5/8"	7"	2.19	21	46.47
WCp-A08	8"	8-5/8"	2.00	16	32.59
WCp-A10	10"	10-3/4"	2.80	12	72.39
WCp-A12	12"	12-3/4"	3.75	10	86.66
Painted Blue WCp-A06-BLUE	6"	6-5/8"	1.50	24	18.54



pC Series "Dicken"  
(1 set screw only)

PERSONALIZED CAPS are available. please contact your Sales Rep for further information and delivery.

## WTC SERIES BII WATERTITE WELL CAPS

- Easy to install, easy access for maintenance
- Greater clearance for submersible pump cable
- O-ring system ensures reliable watertight seal between well casing and retainer ring
- A second O-ring is used to seal cover and retainer ring, a positive compression seal is achieved by tightening 4 bolts
- Grounding terminal with bolt provided
- A well log is provided inside each cap to record installation data/specifications
- Meets with the Water Systems Council (WSC) pAS-97 standard

- Vermin proof with large screened air vents
- Stainless steel hardware

PART NO.	CASING SIZE (IN.)		CONDUIT CONNECTION	AIR VENTS	UNIT wgT (lbs)	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
<b>ALUMINUM</b>							
WTC-A04	4"	4-1/2"	1" FpT	(2) 3/4"	3.00	16	35.75
WTC-A05	5"	5-9/16"	1" FpT	(2) 3/4"	3.25	12	39.06
WTC-A06	6"	6-5/8"	1" FpT	(2) 3/4"	4.00	12	48.06
WTC-A06-BLUE	6"	6-5/8"	1" FpT	(2) 3/4"	4.00	12	53.96
WTC-A06-12	6"	6-5/8"	1-1/4" FpT	(2) 3/4"	4.00	12	52.81
WTC-A06-12-BLUE 6"	6"	6-5/8"	1-1/4" FpT	(2) 3/4"	4.00	12	58.81
WTC-pA06 *	6"	6 5/8"	1" FpT	(2) 3/4"	2.50	12	33.77
<b>CAST IRON - Durable Blue powder Coat paint</b>							
WTC-C06	6"	6-5/8"	1" FpT	(2) 3/4"	9.5	6	60.97
WTC-C06-12	6"	6-5/8"	1-1/4" FpT	(2) 3/4"	9.5	6	62.71

8, 10 and 12" available in locking style only, see WTCL series, Page 11-6



WTC Series



WTC-A06-BLUE  
(Durable powder Coat paint)



\*WTC-pA06  
(pVC cover c/w Alum. lower ring for steel casing)



WTC-C06  
(Durable powder Coat paint)

## WTC-g SERIES BII WATERTITE CAPS FOR PVC WELL CASING

- Same design as the above WTC Series but with exception that the lower ring is plastic which can be solvent welded directly to pVC well casing
- Durable UV stabilized, high impact ABS
- Meet with the Water Systems Council (WSC) pAS-97 standard

PART NO.	CASING SIZE (IN.)		CONDUIT CONNECTION	AIR VENTS	UNIT wgT-lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
WTC-G-p0625	6-1/4"	6.90"	1" FpT	(2) 3/4"	1.75	12	29.85
WTC-G-Ap0625	6-1/4"	6.90"	1" FpT	(2) 3/4"	2.75	12	35.26



WTC-G-p0625  
ABS top with  
ABS glue-on lower ring



WTC-G-Ap0625  
Aluminum top with  
ABS glue-on lower ring

## SWVPC SERIES "SEAL WELL" WATERTITE WELL CAPS

- Vermin proof with screen vents
- Aluminum castings with Stainless Steel nuts and bolts
- A positive compression seal between the well casing and cap as well as the cap cover and retainer ring is achieved by tightening 5 bolts
- A well log is provided inside each cap to record installation data/specifications

PART NO.	CASING SIZE (IN)		CONDUIT CONNECTION	AIR VENTS	UNIT wgT-lbs	CASE QTY	LIST PRICE-A
	I.D.	O.D.					
SWVpCC-5	5"	5-9/16"	1" FpT	(1) 1/2"	2.7	10	73.10
SWVpCC-6	6"	6-5/8"	1" FpT	(1) 1/2"	3.0	10	76.56



## WTCC SERIES WATERTITE CAPS - CAST IRON

- Rugged cast iron construction
- Wide gasket provides a positive compression seal between the well casing and cap as well as the cap cover and retainer ring, compression is achieved by tightening 5 bolts
- Blue paint finish

- Vermin proof with screen vents

PART NO.	CASING SIZE (IN)		CONDUIT CONNECTION	AIR VENTS	CASE QTY	CTN/CASE SHIPPING wgT-lbs	LIST PRICE-A
	I.D.	O.D.					
WTCC-6-CI	6", 6-1/4"	6-5/8"	1" FpT	(1) 1/2"	5	13.25/70	55.20
WTCC-6-CI-12	6", 6-1/4"	6-5/8"	1-1/4" FpT	(1) 1/2"	4	13.25/70	57.92



## wTMLC SERIES BII LOCKING wATERTITE wELL CAPS

### ALUMINUM wATERTITE LOCKING CAPS

- Easy to install, easy access for maintenance
- Vermin proof with large screened air vents
- Stainless steel hardware
- O-ring system to ensure reliable seal to casing
- A second O-ring is used to seal cover and retainer ring, a positive compression seal is achieved by tightening a single set screw on a specially designed tapered surface ensuring a positive seal
- Locking feature provides a secure/tamper-proof installation
- Grounding terminal with bolt provided
- A well log is provided inside each cap to record installation data/specifications
- Meets with the Water Systems Council (WSC) pAS-97 standard

PART NO.	CASING SIZE (IN.)		CONDUIT CONNECTION	AIR VENTS	UNIT wgT-lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
WTMLC-A04	4"	4-1/2"	1" FpT	(2) 3/4"	2.60	20	37.37
WTMLC-A04-BLUE	4"	4-1/2"	1" FpT	(2) 3/4"	2.60	20	42.05
WTMLC-A045	4-1/2"	5"	1" FpT	(2) 3/4"	2.76	16	38.92
WTMLC-A045-BLUE	4-1/2"	5"	1" FpT	(2) 3/4"	2.76	16	44.25
WTMLC-A05	5"	5-9/16"	1" FpT	(2) 3/4"	2.95	16	41.54
WTMLC-A05-BLUE	5"	5-9/16"	1" FpT	(2) 3/4"	2.95	16	46.98
WTMLC-A056	5-5/8"	6"	1" FpT	(2) 3/4"	3.11	16	43.42
WTMLC-A056-BLUE	5-5/8"	6"	1" FpT	(2) 3/4"	3.11	16	48.82
WTMLC-A06	6"	6-5/8"	1" FpT	(2) 3/4"	3.95	12	49.66
WTMLC-A06-BLUE	6"	6-5/8"	1" FpT	(2) 3/4"	3.95	12	56.72
WTMLC-A06-12	6"	6-5/8"	1-1/4" FpT	(2) 3/4"	3.95	12	49.66
WTMLC-A06-12-BLUE	6"	6-5/8"	1-1/4" FpT	(2) 3/4"	3.95	12	57.60
WTMLC-A066	6-5/8"	7"	1" FpT	(2) 3/4"	3.53	12	48.00
WTMLC-A066-BLUE	6-5/8"	7"	1" FpT	(2) 3/4"	3.53	12	66.26

### LOCKING CAPS - ALUMINUM COVER WITH gLUE-ON ABS RING

PART NO.	CASING SIZE (IN.)		CONDUIT CONNECTION	AIR VENTS	UNIT wgT-lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
WTMLC-G-Ap04	4"	4.500"	1" FpT	(2) 3/4"	2.03	20	29.42
WTMLC-G-Ap045	4-1/2"	4.950"	1" FpT	(2) 3/4"	2.18	16	31.58
WTMLC-G-Ap05	5"	5.563"	1" FpT	(2) 3/4"	2.36	16	34.39
WTMLC-G-Ap0625	6-1/4"	6.900"	1" FpT	(2) 3/4"	2.40	12	34.78



Note:  
Locks not included.  
For illustration  
purposes only.



## 8", 10", 12" wTCL SERIES BII wATERTITE LOCKING wELL CAPS

### ALUMINUM wATERTITE LOCKING CAPS

- Easy to install, easy access for maintenance
- Vermin proof with large screened air vents
- Stainless steel hardware
- O-ring system to ensure reliable seal to casing
- A second O-ring is used to seal cover and retainer ring, a positive compression seal is achieved by tightening 6 bolts
- Locking feature provides a secure/tamper-proof installation
- Grounding terminal with bolt provided
- A well log is provided inside each cap to record installation data/specifications

PART NO.	CASING SIZE (IN.)		CONDUIT CONNECTION	AIR VENTS	UNIT wgT-lbs	QTY CASE	LIST PRICE-A
	I.D.	O.D.					
WTCL-A08	8"	8-5/8"	1-1/4" FpT	(2) 3/4"	5.25	8	80.27
WTCL-A10	10"	10-3/4"	1-1/4" FpT	(2) 3/4"	6.00	5	175.10
WTCL-A12	12"	12-3/4"	1-1/4" FpT	(2) 3/4"	6.50	5	226.09



Note:  
Locks not included.  
For illustration  
purposes only.

