

"BII FAST" FORGED BRASS GAS VALVES WITH 1/8" PILOT TAP



5G STANDARD 3.88 (USA)
STANDARD CR91-002 (CAN)
5 PSIG RATED GAS VALVE

1/2PSI ANSI Z21.15 (USA)
CGA 9.1 (CAN)
1/2 PSIG APPLIANCE VALVE

Side Tapped 1/8" for connection to a manometer which allows line pressure to be tested at the valve, eliminating the need for an additional test tee. All pilot tap valves come with a brass plug

Blow-out proof stem CSA approved

PART NO.	SIZE	PORT DIA. INS.	QUANTITY CTN	QUANTITY CASE	LIST PRICE-F
0832TP-05	1/2" FPT x 1/2" FPT	0.400	1	120	10.52
0832TP-07	3/4" FPT x 3/4" FPT	0.600	1	120	15.22
0833TP-0503	1/2" FPT x 3/8" FL	0.400	1	120	14.59
0833TP-0505	1/2" FPT x 1/2" FL	0.400	1	120	14.81
0835TP-03	3/8" FL x 3/8" FL	0.400	1	120	15.36
0835TP-05	1/2" FL x 1/2" FL	0.400	1	120	15.36

"BII FAST" BRASS GAS BALL VALVES



Meets CSA approval
 Meets UL approval
 Yellow Handle



1/2PSI ANSI Z21.15 (USA)
CGA 9.1 (CAN)
1/2 PSIG APPLIANCE VALVE

ANSI AMERICAN NATIONAL STANDARDS INSTITUTE

5G STANDARD 3.88 (USA)
STANDARD CR91-002 (CAN)
5 PSIG RATED GAS VALVE

PART NO.	SIZE	PORT DIA. INS.	QUANTITY CTN	QUANTITY CASE	LIST PRICE-F
FPT x FPT - TWO PIECE BODY DESIGN Forged Brass					
0832-03	3/8"	0.400	12	144	8.68
0832-05	1/2"	0.400	12	144	6.94
0832-07	3/4"	0.600	12	144	9.86
0832-10	1"	0.800	6	60	19.27
FPT x FLARE - TWO PIECE BODY DESIGN Forged Brass					
0833-0503	1/2" FPT x 3/8" FL	0.400	12	144	9.63
0833-0505	1/2" FPT x 1/2" FL	0.400	12	144	9.63
MPT x FLARE - TWO PIECE BODY DESIGN Forged Brass					
0834-0503	1/2" MPT x 3/8" FL	0.400	12	144	10.85
0834-0505	1/2" MPT x 1/2" FL	0.400	12	144	10.85
FLARE x FLARE Forged Brass					
0835-03	3/8" FL X 3/8" FL	0.400	12	144	10.45
0835-05	1/2" FL X 1/2" FL	0.400	12	144	10.45

GAS VALVES

BEST BUY

- Two piece body
- Forged body
- Dual O-ring seal design
- Meets CSA approval
- 600 WOG
- Blow out proof stem
- Yellow handle
- Meets UL approval



PART NO.	SIZE	PORT DIA. INS.	QUANTITY CTN	QUANTITY CASE	LIST PRICE-F
2-0832-03	3/8"	0.3085	10	100	5.03
2-0832-05	1/2"	0.3975	10	100	5.29
2-0832-07	3/4"	0.5740	10	100	8.56

CAN 3.16 CAN / CGA - 3.16 STANDARD
125 PSIG RATING (CAN)
FOR OUTDOOR USE

5G STANDARD 3.88 (USA)
STANDARD CR91-002 (CAN)
5 PSIG RATED GAS VALVE

1/2PSI ANSI Z21.15 (USA)
CGA 9.1 (CAN)
1/2 PSIG APPLIANCE VALVE

BRS125G 125 PSIG RATING (USA)
CGA 9.1 (CAN)
STANDARD 3.88 (USA)

Meets CSA approval



PART NO.	SIZE	PORT DIA. INS.	QUANTITY CTN	QUANTITY CASE	LIST PRICE-F
2-0835-03	3/8" FL X 3/8" FL	0.2815	10	100	4.91
2-0835-05	1/2" FL X 1/2" FL	0.3950	10	100	5.41

1/2PSI ANSI Z21.15 (USA)
CGA 9.1 (CAN)
1/2 PSIG APPLIANCE VALVE

5G STANDARD 3.88 (USA)
STANDARD CR91-002 (CAN)
5 PSIG RATED GAS VALVE