

PVC CLEAR TUBING

FEATURES

- Non-toxic
- Odourless & Taste-free
- Nonconductive
- Fire Resistant
- Self-extinguishing
- FDA Compounds used comply with
- NSF certified under standards NSF 51
- Type 10

TYPICAL APPLICATIONS

- Laboratory
- Food & Beverage
- Drain And Chemical Transfer
- Water And
- Wire Harness
- Sight Gauges
- Light Vacuum Lines



Temperature Range: 25°F (-5°C) to 150°F (65°C)

| PART NO. | SIZE | | LENGTH | WORKING PSI @ 20°C | WALL THICKNESS | WEIGHT PER CFT | LIST PRICE-A PER FOOT |
|--------------|-------|-------|---------|-----------------------|-------------------|-------------------|--------------------------|
| | I.D. | O.D. | | | | | |
| 106-0204-100 | 1/8 | 1/4 | 100 FT. | 65 | .063 | 1.9 LBS | 0.28 |
| 106-0305-100 | 3/16 | 5/16 | 100 FT. | 55 | .063 | 2.6 LBS | 0.32 |
| 106-0406-100 | 1/4 | 3/8 | 100 FT. | 55 | .063 | 3.2 LBS | 0.34 |
| 106-0408-100 | 1/4 | 1/2 | 100 FT. | 60 | .125 | 7.6 LBS | 0.61 |
| 106-0507-100 | 5/16 | 7/16 | 100 FT. | 50 | .063 | 3.8 LBS | 0.39 |
| 106-0608-100 | 3/8 | 1/2 | 100 FT. | 45 | .063 | 4.5 LBS | 0.42 |
| 106-0610-100 | 3/8 | 5/8 | 100 FT. | 55 | .125 | 10.2 LBS | 0.84 |
| 106-0810-100 | 1/2 | 5/8 | 100 FT. | 30 | .063 | 5.7 LBS | 0.54 |
| 106-0812-100 | 1/2 | 3/4 | 100 FT. | 45 | .125 | 12.8 LBS | 1.17 |
| 106-1014-100 | 5/8 | 7/8 | 100 FT. | 40 | .125 | 12.5 LBS | 1.38 |
| 106-1216-100 | 3/4 | 1 | 100 FT. | 35 | .125 | 17.9 LBS | 1.56 |
| 106-1418-100 | 7/8 | 1-1/8 | 100 FT. | 30 | .125 | 20.4 LBS | 2.34 |
| 106-1620-100 | 1 | 1-1/4 | 100 FT. | 25 | .125 | 23.0 LBS | 2.09 |
| 106-2024-100 | 1-1/4 | 1-1/2 | 100 FT. | 20 | .125 | 28.1 LBS | 2.80 |
| 106-2430-100 | 1-1/2 | 1-7/8 | 100 FT. | 30 | .1875 | 51.7 LBS | 5.69 |
| 106-3240-100 | 2 | 2-1/2 | 100 FT. | 35 | .25 | 92.0 LBS | 9.60 |

POLYETHYLENE TUBING - FOOD GRADE

FEATURES

- Type 50
- Lightweight Tubing
- Odourless And Tasteless
- Materials Comply With The F.d.a. Specifications
- Low Density
- Resistance To Stress
- Milky Cracking Colour

TYPICAL APPLICATIONS

- Air Instrumentation
- Water Lines
- Food Transfer
- Transmission Lines
- Chemical Spray
- Beverage And Soda Transfer
- Light Vacuum Line
- Conduit
- Pneumatic Control Tubing



Temperature Range: -40°F (-45°C) to 150°F (65°C)

| COIL PART NO. | LENGTH | LIST-A PER FT. | REEL PART NO. | LENGTH | LIST-A PER FT. | SIZE O.D. I.D. | WORKING PSI | WALL WEIGHT THICK. PER CFT. |
|------------------|---------|-------------------|------------------|----------|-------------------|-------------------|----------------|--------------------------------|
| 105-04H-100 | 100 FT. | 0.26 | 105-04H-2000 | 2000 FT. | 0.26 | 1/4" .125 | 150 | .062 1.5 LBS |
| 105-04-100 | 100 FT. | 0.21 | 105-04-2000 | 2000 FT. | 0.21 | 1/4" .170 | 140 | .040 1.1 LBS |
| 105-06-100 | 100 FT. | 0.36 | 105-06-500 | 500 FT. | 0.36 | 3/8" .250 | 125 | .062 2.5 LBS |
| 105-08-100 | 100 FT. | 0.50 | 105-08-500 | 500 FT. | 0.50 | 1/2" .375 | 100 | .062 3.5 LBS |
| 105-10-100 | 100 FT. | 0.61 | 105-10-500 | 500 FT. | 0.61 | 5/8" .500 | 75 | .062 4.5 LBS |

H - DENOTES HEAVY WALL TUBE

CLEAR BRAIDED P.V.C. HOSE - STANDARD WALL

Please note applications are general. However, the degree of resistance of a material also depends on other variables such as length of exposure, temperature, pressure, velocity of fluid, concentration, etc. and therefore no guarantee is expressed or implied. If an element of doubt exists, we advise that the product be tested under actual conditions. Crystal clear polyvinyl chloride reinforced with spiraled polyester cords. Cover and tube are compounded from Non-Toxic PVC ingredients in compliance with applicable Fda requirements.


FEATURES

- Glass Smooth Interior
- Chemical Resistant
- Self-extinguishing
- Non-marking
- Lightweight
- Ozone & Atmospheric Resistant
- NSF Certified Under Standard NSF-51
- Type 20
- Clear PVC tube. Polyester reinforced
- Flexible
- Tight tolerances
- FDA Compounds used comply with FDA standards

Service Temperature Range: 25°F(-5°C) to 150°F (65°C)

INDUSTRIAL APPLICATIONS

- Pneumatic Lines
- Lubrication Lines
- Air & Water
- Packaging Machines
- Glue Lines
- Air Breathing Lines
- Vacuum Lines
- (Call Factory For Rating)
- deionized Water Systems
- Wire Conduit



| PART NO. | NOMINAL | | MAXIMUM WORKING PRESSURE | | LENGTH IN FEET | APPROX. WGT. PER CFT. | LIST PRICE-A PER FOOT |
|------------|---------|-------|---------------------------|----------------------------|-------------------|-----------------------------|--------------------------|
| | I.D. | O.D. | @ 70°F(21°C) PSI (MPa) | @ 122°F(50°C) PSI (MPa) | | | |
| 107-03-100 | 3/16 | .375 | 250 (1.72) | 150 (1.03) | 100 FT | 4.5 LBS | 0.59 |
| 107-04-100 | 1/4 | .460 | 250 (1.72) | 150 (1.03) | 100 FT | 6.5 LBS | 0.64 |
| 107-05-100 | 5/16 | .525 | 250 (1.72) | 135 (0.93) | 100 FT | 7.5 LBS | 0.76 |
| 107-06-100 | 3/8 | .600 | 225 (1.55) | 125 (0.86) | 100 FT | 9.0 LBS | 0.89 |
| 107-08-100 | 1/2 | .750 | 200 (1.38) | 100 (0.69) | 100 FT | 14.5 LBS | 1.17 |
| 107-08-300 | 1/2 | .750 | 200 (1.38) | 100 (0.69) | 300 FT | 14.5 LBS | 1.17 |
| 107-10-100 | 5/8 | .875 | 200 (1.38) | 100 (0.69) | 100 FT | 16.5 LBS | 1.52 |
| 107-12-100 | 3/4 | 1.030 | 150 (1.03) | 85 (0.58) | 100 FT | 23.0 LBS | 1.88 |
| 107-12-300 | 3/4 | 1.030 | 150 (1.03) | 85 (0.58) | 300 FT | 23.0 LBS | 1.88 |
| 107-16-100 | 1 | 1.312 | 125 (0.86) | 75 (0.52) | 100 FT | 32.0 LBS | 2.41 |
| 107-16-200 | 1 | 1.312 | 125 (0.86) | 75 (0.52) | 200 FT | 32.0 LBS | 2.41 |
| 107-20-050 | 1-1/4 | 1.687 | 100 (0.69) | 55 (0.38) | 50 FT | 58.0 LBS | 4.47 |
| 107-20-100 | 1-1/4 | 1.687 | 100 (0.69) | 55 (0.38) | 100 FT | 58.0 LBS | 4.47 |
| 107-24-050 | 1-1/2 | 1.937 | 100 (0.69) | 50 (0.34) | 50 FT | 69.0 LBS | 5.36 |
| 107-24-100 | 1-1/2 | 1.937 | 100 (0.69) | 50 (0.34) | 100 FT | 69.0 LBS | 5.36 |
| 107-32-050 | 2 | 2.500 | 75 (0.51) | 35 (0.24) | 50 FT | 100.0 LBS | 8.67 |
| 107-32-100 | 2 | 2.500 | 75 (0.51) | 35 (0.24) | 100 FT | 100.0 LBS | 8.67 |