

WARNING FOR CLEAR BOWLS

HANDLE WITH CARE: Scratching, hitting and dropping can cause damage to the clear bowl.
PREVENT FREEZING: Freezing can cause cracks and leaking.
AVOID EXPOSURE TO DIRECT SUNLIGHT
PREVENT EXPOSURE TO SOLVENTS OR SPRAYS: Some sprays and solvents can cause material failure
PROTECT FROM SURGES: If pressure surges are a possibility, install a pressure regulator before the filter to keep pressure below 125 psi.
DO NOT INSTALL FILTER WHERE FAILURE OR LEAKING WOULD CAUSE DAMAGE
FAILURE TO FOLLOW THE ABOVE PRECAUTIONS COULD RESULT IN VOIDING THE WARRANTY
NOT RECOMMENDED FOR USE IN BUILDINGS OVER TEN STORIES.

STANDARD HOUSING PACKAGE

APPLICATIONS

- Water Wells
- Agriculture
- Point of use (Under sink / Taste & Odour)
- Greenhouses / Drip Irrigation
- Main Line Residential Water

Max. Operating Temp:
120°F (50°C)

Max. Operating Pressure:
125 PSI (880 kpa)

Utilizes industry standard
cartridge (not included)



KIT INCLUDES:

- Black polypropylene filter head (c/w pressure relief button)
- Clear styrene-acrylonitrile bowl or Blue polypropylene bowl
- Blue full circle filter wrench
- "L" Style zinc-plated mounting bracket with hardware
- Custom made NBR "O"-ring plus one extra replacement

HOUSING KIT

PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW GPM	DIMENSIONS	SHIPPING WGT-lbs	QUANTITY CTN	CASE	LIST PRICE-A
14HK-S10C-07	3/4" FPT	10" Clear	1 - 10*	12" x 5"	3.3	1	12	26.57
14HK-S10B-07	3/4" FPT	10" Blue	1 - 10*	12" x 5"	3.3	1	12	25.30

ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBS-03	"L" style zinc-plated mounting bracket with hardware	1.60
14A-FWS-03	Blue full circle filter wrench	1.55
14A-ORS-03	NBR "O"-Ring	0.80

REPLACEMENT PARTS

PART NO.	DESCRIPTION	LIST PRICE-A
14PT-SH-07	Black Head	6.47
14PT-SB-10C	Clear Bowl	12.61
14PT-SB-10B	Blue Bowl	12.30

DELUXE FILTER HOUSING PACKAGE

APPLICATIONS

- Water Wells
- Agriculture / Greenhouses
- Lab Equipment
- Food Processing / Service
- Recreational Vehicles
- Drip Irrigation
- Main Line Residential Water
- Photographic
- Vending Equipment

Max. Operating Temp:
120°F (50°C)

Max. Operating Pressure:
125 PSI (880 kpa)

Utilizes industry standard
cartridge (not included)



KIT INCLUDES:

- Black polypropylene filter head (c/w pressure relief button)
- Clear styrene-acrylonitrile bowl or Blue polypropylene bowl
- White polypropylene "C-type" filter wrench
- "L" Style white powder coated steel bracket with hardware
- AS568-242 NBR "O"-ring plus one extra replacement

HOUSING KITS

PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW RATE	DIMENSIONS	SHIPPING WGT-lbs	QUANTITY CTN	CASE	LIST PRICE-A
14HK-D10C-07	3/4" FPT	10" Clear	1 - 10*	12.48" x 5.35"	5.1	1	12	26.58
14HK-D10B-07	3/4" FPT	10" Blue	1 - 10*	12.48" x 5.35"	5.1	1	12	26.58
14HK-D20C-07	3/4" FPT	20" Clear	1 - 25*	23 1/4" x 5 1/2"	6.4	1	6	68.32
14HK-D20B-07	3/4" FPT	20" Blue	1 - 25*	23 1/4" x 5 1/2"	6.4	1	6	51.82

ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBD-03	"L" Style white powder coated steel bracket with hardware	4.68
14A-FWD-03	White polypropylene "C-type" filter wrench	2.30
14A-ORD-242	AS568-242 NBR "O"-Ring	0.84

REPLACEMENT PARTS

PART NO.	DESCRIPTION	LIST PRICE-A
14PT-DH-07	Black Head	8.99
14PT-DB-10C	10" Clear Bowl	12.28
14PT-DB-10B	10" Blue Bowl	10.64
14PT-DB-20C	20" Clear Bowl	56.01
14PT-DB-20B	20" Blue Bowl	45.63

*Actual maximum flow rates vs. pressure drop will be determined based on cartridge selections and fluid viscosity.

VALVE-IN-HEAD PACKAGE

APPLICATIONS

- | | |
|---|--|
| <input type="checkbox"/> Water Wells | <input type="checkbox"/> Drip Irrigation |
| <input type="checkbox"/> Agriculture / Green Houses | <input type="checkbox"/> Main Line Residential Water |
| <input type="checkbox"/> Lab Equipment | <input type="checkbox"/> Photographic |
| <input type="checkbox"/> Food Processing / Service | <input type="checkbox"/> Vending Equipment |
| <input type="checkbox"/> Recreational Vehicles | |

KIT INCLUDES:

- Blue reinforced polypropylene filter head
- On, Off and By Pass positions built into head
- Clear styrene-acrylonitrile bowl or Blue polypropylene bowl
- Blue polypropylene full circle filter wrench
- "U" Style mounting bracket with hardware
- Custom made NBR "O"-ring plus one extra replacement

Max. Operating Temp:
120°F (50°C)

Max. Operating Pressure:
125 PSI (880 kpa)

Utilizes industry standard
cartridge (not included)



HOUSING KIT

PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW GPM	DIMENSIONS	SHIPPING WGT-lbs	QUANTITY		LIST PRICE-A
						CTN	CASE	
14HK-V10C-07	3/4" FPT	10" Clear	1 - 10*	13.78" x 5.16"	3.7	1	12	40.79
14HK-V10B-07	3/4" FPT	10" Blue	1 - 10*	13.78" X 5.16"	3.7	1	12	40.79

ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A	REPLACEMENT PARTS		
			PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBU-01	"U" Style mounting bracket with hardware	4.28	14PT-VH-07	Blue Head	15.80
14A-FWS-03	Blue polypropylene full circle filter wrench	1.55	14PT-VB-10C	Clear Bowl	13.11
14A-ORS-03	Custom made NBR "O"-Ring	0.80	14PT-VB-10B	Blue Bowl	13.11

GIANT HOUSING PACKAGE

APPLICATIONS

- | | |
|---|--|
| <input type="checkbox"/> Water Wells | <input type="checkbox"/> Drip Irrigation |
| <input type="checkbox"/> Restaurants | <input type="checkbox"/> Whole House |
| <input type="checkbox"/> R.O. Systems | <input type="checkbox"/> Institutions |
| <input type="checkbox"/> Spas and Hot Tubs | <input type="checkbox"/> Agriculture |
| <input type="checkbox"/> Food Processing | <input type="checkbox"/> Industrial / Commercial |
| <input type="checkbox"/> Milling Machines | <input type="checkbox"/> Greenhouses |
| <input type="checkbox"/> Vending Machines | <input type="checkbox"/> Plating |
| <input type="checkbox"/> EDM Machines (Water Based) | |

Maximum Operating Temp:
120°F (50°C)

Maximum Operating Pressure:
For 10" Bowl: 100 PSI (700 kpa)
For 20" Bowl: 90 PSI (630 kpa)

Utilizes industry standard
cartridge (not included)



KIT INCLUDES:

- Black polypropylene filter head (c/w pressure relief button)
- Blue polypropylene filter bowl
- Black polypropylene full circle filter wrench
- "L" Style white powder coated steel mounting bracket with hardware
- AS568-358 EPDM "O"-ring plus one extra replacement

HOUSING KITS

PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW GPM	DIMENSIONS	SHIPPING WGT-lbs	QUANTITY		LIST PRICE-A
						CTN	CASE	
14HK-G10B-07	3/4" FPT	10" Blue	1 - 15*	14.05" x 7.28"	8.7	1	4	77.97
14HK-G10B-10	1" FPT	10" Blue	1 - 20*	14.05" x 7.28"	8.7	1	4	77.97
14HK-G10B-15	1-1/2" FPT	10" Blue	1 - 25*	14.05" x 7.28"	8.7	1	4	77.97
14HK-G20B-07	3/4" FPT	20" Blue	1 - 35*	24" x 7.28"	11.2	1	4	126.58
14HK-G20B-10	1" FPT	20" Blue	1 - 40*	24" x 7.28"	11.2	1	4	126.58
14HK-G20B-15	1-1/2" FPT	20" Blue	1 - 50*	24" x 7.28"	11.2	1	4	126.58

ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A	REPLACEMENT PARTS		
			PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBG-03	"L" -style white powder coated steel mounting bracket with hardware	31.11	14PT-GH-07	Black Head	17.24
14A-FWG-03	Black polypropylene full circle filter wrench	5.89	14PT-GH-10	Black Head	17.24
14A-GOR-358	AS568-358 EPDM "O"-ring	1.31	14PT-GH-15	Black Head	17.24
			14PT-GB-10B	Blue Bowl	40.59
			14PT-GB-20B	Blue Bowl	89.58

*Actual maximum flow rates vs. pressure drop will be determined based on cartridge selections and fluid viscosity.

GIANT CLEAR SUMP FILTER HOUSINGS

APPLICATIONS

- Water Wells
- Drip Irrigation
- Greenhouses
- Whole House
- Agriculture

FEATURES / CONSTRUCTION / RATINGS

- Manufactured from FDA grade material for potable water
- Head comes with dual 1" FPT and 1-1/2" FPT threads on both inlet and outlet connections, c/w pressure relief / bleed button on inlet side
- Positive "stop" in white polypropylene head and clear styrene acrylonitrile (SAN) bowl connecting threads prevents overtightening of filter bowl
- Securely retained "O"-ring ensures an effective seal between head and bowl, eliminating potential leaks due to accidental misplacement of "O"-ring
- Mounting bosses molded in head for available mounting bracket
- Accepts industry standard cartridge size
- Max. Operating Temp: 125°F (52°C) Max. Operating Pressure: 125 PSI at 70°F (21°C)



PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW GPM	DIMENSIONS	SHIPPING WGT-lbs	QTY CASE	LIST PRICE-A
14H-G10C-1015	1" & 1-1/2" FPT	10" Clear	1 - 20*	12-1/8" x 10"	4.1	1	143.83
14H-G20C-1015	1" & 1-1/2" FPT	20" Clear	1 - 25*	22-1/2" x 7-1/2"	7.1	1	198.09

ACCESSORIES / REPLACEMENT PARTS

PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBG-03	"L" -style white powder coated steel mounting bracket with hardware	31.11
14A-GFW-01	Giant universal black plastic filter wrench	7.95
14A-GOR-01	B358 Buna-N replacement "O"-ring	4.53

HIGH TEMPERATURE HOUSING PACKAGE

APPLICATIONS

- Hot Water / Liquids
- Alcohols
- Vegetable Oils
- Salt Water Fisheries
- Gasoline
- Photographic
- Toluene / Xylene

Maximum Operating Temp:
200°F(93°C)

Max. Operating Pressure:
125 PSI (880 kpa)

Utilizes industry standard
high temperature cartridge
(not included)

KIT INCLUDES:

- Red reinforced polypropylene head (c/w pressure relief button)
- Red reinforced polypropylene bowl
- White polypropylene "C-type" wrench
- "L" Style white powder coated steel bracket with hardware
- AS568-242 silicone "O"-ring plus one extra replacement



HOUSING KITS

PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW GPM	DIMENSIONS	SHIPPING WGT-lbs	QUANTITY CTN CASE	LIST PRICE-A
14HK-HT10R-07	3/4" FPT	10" Red	1 - 10*	12.48" x 5.35"	4.9	1 12	79.10

ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBD-03	"L" Style white powder coated steel bracket with hardware	4.83
14A-FWD-03	White polypropylene "C-type" filter wrench	2.21
14A-ORHT-242	AS568-242 silicone "O"-ring	1.08

REPLACEMENT PARTS

PART NO.	DESCRIPTION	LIST PRICE-A
14PT-HH-07	Red Head	21.55
14PT-HB-10R	Red Bowl	41.78

*Actual maximum flow rates vs. pressure drop will be determined based on cartridge selections and fluid viscosity.

GIANT HIGH TEMPERATURE HOUSINGS

APPLICATIONS

Suitable for hot water / high pressure service. These glass reinforced nylon housings offer an economical, lightweight, high capacity alternative to metallic vessels. Their economical price allows you to install a preferred "duplex system" for totally uninterrupted flow in a wide variety of applications.

- | | | | |
|--|---------------------------------------|---|---|
| <input type="checkbox"/> Hot Water / Liquids | <input type="checkbox"/> Alcohols | <input type="checkbox"/> Vegetable Oils | <input type="checkbox"/> Salt Water Fisheries |
| <input type="checkbox"/> Gasoline | <input type="checkbox"/> Photographic | <input type="checkbox"/> Toluene / Xylene | |

FEATURES / CONSTRUCTION / RATINGS

- Head comes with dual 1" FPT and 1-1/2" FPT threads on both inlet and outlet connections, high temperature heads are not available with pressure relief / bleed button
- Positive "stop" in black glass reinforced nylon head and bowl connecting threads prevents overtightening of filter bowl
- Securely retained "O"-ring ensures an effective seal between head and bowl, eliminating potential leaks due to accidental misplacement of "O"-ring
- Mounting bosses molded in head for available mounting bracket
- Utilizes industry standard cartridges
- Max. Operating Temp: 200°F (93°C), Max. Operating Pressure: 200 PSI



PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW GPM	DIMENSIONS	SHIPPING WGT-lbs	QTY CASE	LIST PRICE-A
14H-GHT10BK-1015	1" & 1-1/2" FPT	10" Black	1 - 20*	12 1/8" x 10"	5.88	1	353.10
14H-GHT20BK-1015	1" & 1-1/2" FPT	20" Black	1 - 25*	22 1/2" x 7 1/2"	8.25	1	483.29

ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A
14A-MBG-03	"L" -style white powder coated steel mounting bracket with hardware	31.11
14A-GFW-01	Giant universal black plastic filter wrench	7.95
14A-GOR-01	B358 Buna-N replacement "O"-ring	4.43

EXTREME TEMP. / PRESSURE SINGLE TUBE STAINLESS STEEL HOUSING PACKAGE

APPLICATIONS

- | | | | | |
|--------------------------------------|--|---|--------------------------------|-----------------------------------|
| <input type="checkbox"/> Restaurants | <input type="checkbox"/> Institutional | <input type="checkbox"/> Industrial Use | <input type="checkbox"/> Farms | <input type="checkbox"/> Chemical |
|--------------------------------------|--|---|--------------------------------|-----------------------------------|

FEATURES / CONSTRUCTION / RATINGS

- Recommended for high pressure and hot water applications not suited for plastic housings
- These heavy duty units for point of use, and smaller filtration systems are manufactured from 316 stainless steel bowl with a 3/4" FPT connection SS head
- Positive seal between filter head & bowl is ensured by a compression fit O-ring seal. Filter head is held in place by a Stainless Steel retainer ring.
- All units are supplied with a pipe plug in the bottom for draining the bowl, this plug can be replaced with a pet-cock. However, the max operating pressure will be reduced to the operating pressure of the pet-cock installed
- Shipped complete with SS mounting bracket, hardware & wrench
- Accepts industry standard cartridge size
- Maximum Operating Temp: 300°F (149°C) (300°F string wound cartridge available, page 5-10)
- Maximum Operating Pressure: 300 PSI when filter has pipe plug installed



PART NO.	INLET/OUTLET	BOWL LENGTH	FLOW GPM	DIMENSIONS	SHIPPING WGT-lbs	QUANTITY CASE CTN	LIST PRICE-A
14HK-SS10-07	3/4" FPT	10"	1 - 10*	12-7/8" x 4-1/8"	5.4	1 12	252.15
14HK-SS20-07	3/4" FPT	20"	1 - 15*	22-3/4" x 4-1/8"	7.5	1 6	385.65

*Actual maximum flow rates vs. pressure drop will be determined based on cartridge selections and fluid viscosity.

NOTE: Multi-tube available. Please call your Sales Representative for pricing.

ACCESSORIES

PART NO.	DESCRIPTION	LIST PRICE-A	PART NO.	DESCRIPTION	LIST PRICE-A
14A-FWSS-03	Filter Wrench S.S. Housing	2.22	14A-ORSS-03	"O" Ring For S.S.housing-viton	11.29
14A-LRSS-03	L Ring Seal S.S.housing-viton	11.29	14A-MBSS-03	Mounting Bracket S.S. Housing	6.12

CAST IRON SAND STRAINER - 100 MESH

A low cost solution to screen out sediment, grit and dirt from a high flow water supply. Can be installed on either the suction or discharge side of pump with minimal pressure drop. Body and cap are manufactured from a cast iron with a 2-part epoxy finish, a clear plastic filter bowl which allows for visual inspection and furnished with a washable 100 mesh stainless steel screen. These filters are easily cleaned. When used as a pre-filter, the life of your taste and odour cartridges can be dramatically extended.

Max Vacuum 30" hg Max Pressure 100 PSI Max Temp 130°F (55°C)

PART NO.	DESCRIPTION	QUANTITY	LIST PRICE-A
14-SS-100	1-1/4" FPT Connection 100 Mesh Screen	1 15	54.84



REPLACEMENT PARTS

PART NO.	DESCRIPTION	LIST PRICE-A	PART NO.	DESCRIPTION	LIST PRICE-A
14-SSRS-100	100 Mesh S.S. Screen	13.93	14-SSOR	"O"-Rings (2-Per Strainer)	1.18
14-SSRG	Plastic Viewing Sleeve	5.78	14-SSNW	Nylon Washer	0.61
14-SSC	Cast Iron Cover	5.68	14-SSWN	Brass Wing Nut	2.94