

SEDIMENT FAUCETS - O-RING SEALING DESIGN - CSA APPROVED

□With O-ring design, the seal is below the threads. The threads are never exposed to the water whereas packing style valves have the thread constantly submerged in water. O-ring design tends to have easier operation and longevity due to the fact that threads do not become corroded in aggressive water conditions.

□To prevent damage to O-rings, stem must be removed before soldering.



PART NO.	LIST PRICE-F	PART NO.	LIST PRICE-F	SIZE	QUANTITY CTN	QUANTITY CASE
Handle		Handle				
Blue Triangular		Zinc Silver				
0845SF-05	6.24	0846SF-05	6.48	1/2"	10	100
0845SF-07	6.63	0846SF-07	6.87	3/4"	10	100
ANGLE VALVE						
PART NO.	SIZE	QUANTITY CTN	QUANTITY CASE	LIST PRICE-F		
0845SFA-05	1/2"	12	144	6.87		

Maximum Operating Temp:
180°F(82°C)
Pressure Rating:
150 PSI

CSA approved

STOP/STOP & WASTE - O-RING SEALING DESIGN - CSA APPROVED

□With O-ring design, the seal is below the threads. The threads are never exposed to the water whereas packing style valves have the thread constantly submerged in water. O-ring design tends to have easier operation and longevity due to the fact that threads do not become corroded in aggressive water conditions.

□To prevent damage to O-rings, stem must be removed before soldering.



PART NO.	LIST PRICE-F	PART NO.	LIST PRICE-F	SIZE	QUANTITY CTN	QUANTITY CASE
Handle		Handle				
Blue Triangular		Zinc Silver				
STOP						
0845SC-05	6.04	0846SC-05	6.28	1/2"	10	100
STOP & WASTE						
0845SWC-05	6.40	0846SWC-05	6.63	1/2"	10	100

Maximum Operating Temp:
180°F(82°C)
Pressure Rating:
150 PSI

CSA approved

CAST BRASS BOILER DRAINS/SEDIMENT FAUCETS - CSA APPROVED

□Maximum operating temperature:180°F(82°C)

□Pressure rating: 150 PSI

□Black hand wheel

□CSA approved

□Meets NSF approval



PART NO.	LIST PRICE-F	PART NO.	LIST PRICE-F	SIZE	QUANTITY CTN	QUANTITY CASE
MALE THREAD		FEMALE THREAD				
0853-05	7.16	0853F-05	6.87	1/2"	10	100
0853-07	7.39	0853F-07	7.43	3/4"	10	100

CAST BRASS STOP/STOP & WASTE VALVES - CSA APPROVED

□Maximum operating temperature:180°F(82°C)

□Pressure rating: 150 PSI

□Meets NSF 61-8 approval

□Black hand wheel

□CSA approved



STOP VALVE PART NO.	LIST PRICE-F	STOP & WASTE PART NO.	LIST PRICE-F	SIZE	QUANTITY CTN	QUANTITY CASE
0844C						
0843-05	7.69	0844-05	8.00	1/2"	10	100
0843-07	8.49	0844-07	8.80	3/4"	10	100
CxC						
0843C-05	6.54	0844C-05	6.90	1/2"	10	100
0843C-07	7.83	0844C-07	7.91	3/4"	10	100

CROSS HANDLE BRASS STOP VALVES

□Maximum operating temperature:180°F(82°C)

□Pressure rating up to 150 PSI

□CSA approved

□Meets NSF approval



PART NO.	SIZE	QUANTITY CTN	QUANTITY CASE	LIST PRICE-F
0843CH-05	1/2"	10	100	8.45
0843CH-07	3/4"	10	100	9.20

COMPRESSION BRASS STOP & WASTE VALVES - CSA APPROVED



- Maximum operating temperature: 180°F(82°C)
- Black hand wheel
- Rubber packing
- Pressure rating: 150 PSI
- CSA approved

COMPRESSION TO COMPRESSION

PART NO.	SIZE	QUANTITY CTN	QUANTITY CASE	LIST PRICE-F
0844CPR-05	1/2"	10	100	9.10
0844CPR-07	3/4"	10	100	12.04

"BII FAST" CAST BRASS BOILER DRAINS/SEDIMENT FAUCETS - CSA APPROVED



- Maximum operating temperature: 212°F(100°C)
- Pressure rating up to 125 PSI
- Blue cast hand wheel
- Meets ANIS/NSF 61-9 approval
- CSA does not apply to Pex End

PART NO.	LIST PRICE-F	PART NO. PEX	LIST PRICE-F	SIZE	QUANTITY CTN	QUANTITY CASE
0851-05	7.16	0851P-05	9.85	1/2"	10	100
0851-07	7.90			3/4"	10	100

CAST BRASS STOP/STOP & WASTE VALVES - CSA APPROVED



- Maximum operating temperature: 212°F(100°C)
- Pressure rating up to 125 PSI
- Blue cast hand wheel

STOP VALVE PART NO.	LIST PRICE-F	STOP & WASTE PART NO.	LIST PRICE-F	SIZE	QUANTITY CTN	QUANTITY CASE
		0842-05	8.37	1/2"	10	100
		0842-07	10.20	3/4"	10	100
CxC						
0841C-05	7.06	0842C-05	7.36	1/2"	10	100
0841C-07	8.65	0842C-07	9.08	3/4"	10	100

PEX STOP/STOP & WASTE VALVES



- Maximum operating temperature: 180°F(82°C)
- Pressure rating up to 150 PSI

PART NO. PEX	LIST PRICE-F	PART NO.	LIST PRICE-F	SIZE	QUANTITY CTN	QUANTITY CASE
0841P-05	9.26	0842P-05	9.77	1/2"	10	100
0841P-07	9.57	0842P-07	10.08	3/4"	10	100

BENT NOSE VALVES - CSA APPROVED



- Black cast iron hand wheel
- Brass Body
- Maximum operating temperature: 180°F(82°C)
- Pressure rating up to 150 PSI
- CSA approved

PART NO.	SIZE	QUANTITY CTN	QUANTITY CASE	LIST PRICE-F
0872-05	1/2"	10	100	10.14
0872-07	3/4"	10	100	10.14
0872-10	1"	10	100	10.61

BII SILLCOCK - CSA APPROVED



- For cold water applications only
- Maximum operating temperature: 180°F(82°C)
- CSA approved
- Pressure rating up to 150 PSI

PART NO. THREADED	LIST PRICE-F	PART NO. CXC	LIST PRICE-F	SIZE	QUANTITY CTN	QUANTITY CASE
0873-05	6.48	0873C-05	7.47	1/2"	10	100
0873-07	7.27	0873C-07	6.83	3/4"	10	100

ROUGH BRASS HOSE BIBBS



- Maximum operating temperature:180°F(82°C)
- Pressure rating up to 150 PSI
- ANSI NSF 61-8 Approved

PART NO.	INLET CONN.	QUANTITY		LIST PRICE-F
		CTN	CASE	
0871-05	1/2" MPT	10	100	6.00
0871-07	3/4" MPT	10	100	6.71

ROUGH BRASS HOSE BIBBS (NO GARDEN HOSE ATTACHMENT)



- Sampling Faucet
- Maximum operating temperature:180°F(82°C)
- Pressure rating up to 150 PSI
- ANSI NSF 61-8 Approved

PART NO.	INLET CONN.	QUANTITY		LIST PRICE-F
		CTN	CASE	
0874-05	1/2" MPT	10	100	5.80
0874-07	3/4" MPT	10	100	6.67

1/4 TURN BALL HOSE BIBBS



- Maximum operating temperature: 248°F(120°C)
- Pressure rating up to 200 PSI
- Blue cast tee handle

PART NO.	SIZE		QUANTITY		LIST PRICE-F
	INLET	OUTLET	CTN	CASE	
0852-05	1/2" MPT	3/4" MGHT	10	100	9.02
0852-07	3/4" MPT	3/4" MGHT	10	100	10.30

STAINLESS STEEL 1/4 TURN BALL HOSE BIBBS



PART NO.	SIZE		QUANTITY		LIST PRICE-F
	INLET	OUTLET	CTN	CASE	
SSHB52-05	1/2" MPT	3/4" GHT	10	100	15.18
SSHB52-07	3/4" MPT	3/4" GHT	10	100	18.29

PLASTIC HOSE BIBBS



- White ABS Material
- Hose Thread Outlet
- Red T-Handle
- Pressure Rating 145 PSI

PART NO.	SIZE		QUANTITY		LIST PRICE-F
	INLET	OUTLET	CTN	CASE	
PHB-05	1/2" MPT	3/4" GHT	100	200	2.76
PHB-07	3/4" MPT	3/4" GHT	100	200	3.21

1/4 TURN SAMPLING FAUCETS (NO GARDEN HOSE ATTACHMENT)



- Maximum operating temp.:248°F(120°C)
- Pressure rating up to 200 PSI
- Blue cast tee handle

PART NO.	SIZE	QUANTITY		LIST PRICE-F
		CTN	CASE	
0852SF-05	1/2" MPT	10	100	9.02
0852SF-07	3/4" MPT	10	100	10.30