

PVC COMPRESSION FITTINGS - IRON & PVC PIPE SIZE



NOTE:
Pipes must be properly restrained or end blocked to prevent blow off after installation.

COUPLINGS

PSI @ 73°F (23°C)

Nitrile Seal

Rated @ 150

PART NO.	IPS SIZE	BODY LENGTH	OUTSIDE DIAMETER	CASE WT lbs	QUANTITY CTN	CASE PRICE-A
29-CC05	1/2"	5.236"	1.850"	27.2	1 100	1.45
29-CC07	3/4"	5.315"	2.086"	31.3	1 90	1.69
29-CC10	1"	5.748"	2.402"	29.3	1 60	2.21
29-CC12	1-1/4"	6.299"	2.874"	26.2	1 40	2.49
29-CC15	1-1/2"	6.890"	3.150"	26.5	1 30	3.38
29-CC20	2"	7.874"	3.622"	24.8	1 20	4.63
29-CC25	2-1/2"	9.921"	4.528"	22.7	1 10	10.74
29-CC30	3"	10.866"	5.276"	12.9	1 4	16.17
29-CC40	4"	11.929"	6.339"	9.9	1 2	21.68
29-CC60	6"	11.220"	8.780"	15.7	1 2	39.46

CPVC COUPLINGS

Nitrile Seal

Rated @ 150 PSI @ 73°F (23°C)/45 PSI @ 180°F(82°C)



PART NO.	CTS SIZE	DESCRIPTION	LENGTH	CASE WT lbs	QUANTITY CTN	LIST PRICE-A
29CTS-CC05	1/2"	1/2CTS x 1/2CTS	4.488"	55.4	20 360	2.81
29CTS-CC07	3/4"	3/4CTS x 3/4CTS	5.000"	72.6	20 240	4.21

PVC COMPRESSION FITTINGS - IRON & PVC PIPE SIZE



PVC COUPLINGS

Buna-N Seal

200 PSI Rated

PART NO.	IPS SIZE	BODY LENGTH	CTN WT lbs	QTY CTN	LIST PRICE-A
29-110-10	1"	4-1/2"	7.5	15	5.34
29-110-12	1-1/4"	5"	7.5	10	8.28
29-110-15	1-1/2"	5-1/2"	15.5	16	8.55
29-110-20	2"	6"	15.5	12	11.56
29-110-25	2-1/2"	8"	6.0	3	20.97
29-110-30	3"	9"	9.9	3	28.12
29-110-40	4"	10"	13.5	3	45.08
29-110-60	6"	10"	7.0	1	101.51



COUPLINGS WITH FLO-LOCK

EPDM O-Rings

Rated @ 160 PSI @ 72°F

PART NO.	IPS SIZE	BODY LENGTH	CTN WT lbs	QTY CTN	LIST PRICE-A
29-112-05	1/2"	4"	8.5	28	4.34
29-112-07	3/4"	4-1/4"	9.5	24	5.82
29-112-10	1"	4-1/2"	7.5	15	7.68
29-112-12	1-1/4"	5"	7.0	10	11.44
29-112-15	1-1/2"	5-1/2"	15.0	16	11.17
29-112-20	2"	6"	15.0	12	15.57

NOTE: Not recommended for use on systems exceeding 100 PSI at 120°F (48°C)

PVC COMPRESSION FITTINGS - IRON & PVC PIPE SIZE



COUPLINGS

Buna-N Seal

200 PSI Rated @ 72°F

PART NO.	CTS SIZE	BODY LENGTH	CTN WT lbs	QTY CTN	LIST PRICE-A
29-210-05	1/2"	4"	3.7	25	3.60
29-210-07	3/4"	4-1/4"	8.0	28	4.48
29-210-10	1"	4-1/4"	9.0	24	5.55
29-210-12	1-1/4"	4-1/2"	8.5	15	7.84
29-210-15	1-1/2"	5"	7.5	10	10.69
29-210-20	2"	6"	13.5	12	14.83

NOTE: Not recommended for use on systems exceeding 100 PSI at 120°F

PVC COMPRESSION FITTINGS - COPPER TUBE SIZE



CTS MALE ADAPTERS WITH FLOLOCK

EPDM O-Rings

Rated @ 160 PSI @ 72°F

PART NO.	CTS SIZE	IPS CONNECTION	CTN WT lbs	QTY CTN	LIST PRICE-A
29-235-05	1/2"	1/2" MPT	4.0	50	4.72
29-235-07	3/4"	3/4" MPT	3.5	25	5.02
29-235-10	1"	1" MPT	3.3	18	6.00

NOTE: Not recommended for use on systems exceeding 100 PSI at 120°F

FLO-SPAN PVC EXPANSION COUPLINGS - UNION STYLE



200 PSI Rated @ 72°F

PART NO.	IPS SIZE	MAXIMUM EXTENSION	BODY LENGTH	QTY CTN	LIST PRICE-A
29-117-05	1/2"	2"	5-3/4"	28	4.68
29-117-07	3/4"	2-1/4"	6-3/4"	24	4.88
29-117-10	1"	2-1/2"	7-3/4"	15	5.75
29-117-12	1-1/4"	2-5/8"	9"	10	10.62
29-117-15	1-1/2"	3"	10"	16	11.63
29-117-20	2"	3"	10-1/2"	12	18.16

PRO-SPAN PVC EXPANSION COUPLINGS - NON-UNION STYLE



200 PSI Rated @ 72°F

PART NO.	IPS SIZE	MAXIMUM EXTENSION	BODY LENGTH	QTY CTN	LIST PRICE-A
29-118-25	2-1/2"	4-3/16"	13"	3	29.06
29-118-30	3"	4-3/16"	14-1/2"	3	36.33
29-118-40	4"	4-3/16"	14-1/2"	3	63.52

PVC EXPANSION COUPLINGS - UNION STYLE


150 PSI Rated @ 73°F

- ☐ PVC body, nut and plunger
- ☐ NBR O-rings
- ☐ Solvent weld connections



NOTE: Recommended for cold water applications only.

PART NO.	IPS SIZE	PORT (TUBE) I.D.	BODY LENGTH (L)		OUTSIDE SOCKET SPIGOT DIA. (D1) I.D. (D2) O.D. (D4)			QTY CTN	LIST PRICE-A
				EXTENDED					
29-EC05	1/2"	0.50"	6.654"	8.688"	1.890"	0.850"	0.839"	90	4.48
29-EC07	3/4"	0.75"	7.559"	9.803"	2.126"	1.063"	1.043"	60	4.90
29-EC10	1"	1.00"	8.700"	11.378"	2.600"	1.327"	1.307"	40	6.24
29-EC12	1-1/4"	1.25"	9.763"	12.520"	2.992"	1.673"	1.654"	30	11.14
29-EC15	1-1/2"	1.50"	9.882"	12.874"	3.228"	1.913"	1.890"	20	12.74
29-EC20	2"	2.00"	11.300"	14.370"	3.701"	2.390"	2.370"	16	18.55
29-EC25	2-1/2"	2.50"	12.622"	16.870"	4.224"	2.889"	2.875"	4	27.22
29-EC30	3"	3.00"	13.465"	17.579"	4.957"	3.516"	3.50"	3	35.88
29-EC40	4"	4.00"	14.795"	19.331"	6.146"	4.518"	4.50"	2	65.79



FLO CLAMP-IT - IPS PVC PIPE SIZES

PART NO. THREADED (FPT) OUTLET	LIST PRICE-A	PART NO. SLIP (ANSI) OUTLET	LIST PRICE-A	OUTLET SIZE	CTN WT lbs	QTY CTN
2" IRON PIPE SIZE (IPS)						
29-4220-07	27.96	29-4320-07	25.02	3/4"	4.5	5
29-4220-10	27.96	29-4320-10	25.02	1"	4.5	5
29-4220-12	27.96	29-4320-12	25.02	1-1/4"	4.5	5
29-4220-15	27.96	29-4320-15	25.02	1-1/2"	4.5	5
2-1/2" IRON PIPE SIZE (IPS)						
29-4225-07	31.99			3/4"	5	5
29-4225-10	31.99	29-4325-10	33.93	1"	5	5
29-4225-12	30.71			1-1/4"	5	5
29-4225-15	31.99	29-4325-15	33.93	1-1/2"	5	
29-4225-20	31.99	29-4325-20	33.93	2"	5	5
3" IRON PIPE SIZE (IPS)						
29-4430-07	38.22	29-4530-07	33.93	3/4"	8.5	5
29-4430-10	38.22	29-4530-10	33.93	1"	8.5	5
29-4430-12	38.22	29-4530-12	33.93	1-1/4"	8.5	5
29-4430-15	38.22	29-4530-15	33.93	1-1/2"	8.5	5
29-4430-20	38.22	29-4530-20	33.93	2"	8.5	5
4" IRON PIPE SIZES (IPS)						
29-4440-07	48.13	29-4540-07	43.48	3/4"	9.5	5
29-4440-10	48.13	29-4540-10	43.48	1"	9.5	5
29-4440-12	48.13			1-1/4"	9.5	5
29-4440-15	48.13	29-4540-15	43.48	1-1/2"	9.5	5
29-4440-20	48.13	29-4540-20	43.48	2"	9.5	5
6" IRON PIPE SIZES (IPS)						
29-4460-07	70.17	29-4560-07	70.17	3/4"	11	5
29-4460-10	70.17	29-4560-10	70.17	1"	11	5
29-4460-12	70.17			1-1/4"	11	5
29-4460-15	70.17	29-4560-15	70.17	1-1/2"	11	5
29-4460-20	70.17	29-4560-20	70.17	2"	11	5
8" IRON PIPE SIZES (IPS)						
29-4480-07	85.15	29-4580-07	81.74	3/4"	18	5
29-4480-10	85.15	29-4580-10	85.15	1"	18	5
29-4480-15	85.15	29-4580-15	85.15	1-1/2"	18	5
29-4480-20	85.15	29-4580-20	85.15	2"	18	5



Pressure Rated
200 PSI @ 72°F (22°C)

NOTE: Not
recommended for
use on systems
exceeding
100 PSI at 120°F